

Plankit™



WHY Plankit™ PRODUCTS?

With Plankit, elevate your home décor to a whole new aesthetic, allowing you to express your unique style in every space. Experience unparalleled versatility, enabling you to effortlessly upgrade your home with ease.

PARAMETERS	Plankit™	LVT	WOODEN FLOORING
Anti-Fade	✓	✗	✗
Higher Abrasion	✓	✗	✗
Ease of Multi-surface application	✓	✓	✗
Ease of Multi-Laying pattern	✓	✓	✗
No affect by changes in moisture & temperature	✓	✓	✗
Increased Stability & Durability	✓	✗	✗
Waterproof	✓	✓	✗

*T&C Apply

Structure

Plankit is the perfect choice for those who crave long-lasting durability, waterproofness, and resistance against shattering, scratches, and stains. It seamlessly combines the strength of polymer and stone with a flexi core, giving you the best of both worlds. With its versatile multi-laying patterns and multi-surface applicability, you can effortlessly achieve the desired look while relishing in its timeless beauty for years to come.



Features



WELSPUN SPC
FLOORING 2.00 MM
HFO01831

The background of the image is a dark, textured surface with a wood grain pattern. The grain runs vertically, with various shades of brown and grey, creating a natural, organic appearance. There are some lighter spots and knots visible in the wood grain.

WELSPUN SPC
FLOORING 2.00 MM
HF001832



WELSPUN SPC
FLOORING 2.00 MM
HF001833 .

The background of the image is a vertical wood-grain texture, likely representing a laminate or SPC flooring. The wood grain is light brown with darker, wavy patterns and several small, dark knots or imperfections scattered throughout. The texture is consistent and covers the entire frame.

WELSPUN SPC
FLOORING 2.00 MM
HF001834



WELSPUN SPC
FLOORING 2.00 MM
HF001835

WELSPUN SPC
FLOORING 2.00*MM
HF001836



WELSPUN SPC
FLOORING 2.00 MM
HF001837



WELSPUN SPC
FLOORING 2.00 MM
HF001838

WELSPUN SPC
FLOORING 2.00 MM
HF001839

WELSPUN SPC
FLOORING 2.00 MM
HF001840

The image shows a close-up of several vertical planks of grey wood-grain SPC flooring. The planks have a realistic wood grain pattern with various knots and textures. A prominent vertical crack runs down the center of the image, separating two planks. The overall color is a muted, greyish-brown.

WELSPUN SPC
FLOORING 2.00 MM
HF001841

WELSPUN SPC
FLOORING 2.00•MM
HF001842

The image shows a close-up of a light-colored wood-grain SPC flooring. The texture is highly detailed, showing natural wood grain patterns, including knots and wavy lines. A vertical seam or joint is visible on the right side of the image. The overall color is a warm, light beige or tan.

WELSPUN SPC
FLOORING 2.00 MM
HF001843

Technical Characteristics

TEST DESCRIPTION	TEST METHOD	TEST RESULT
Dimensional Stability	ISO 23999	Machine Direction : 0.4" Cross Direction : 0.12"
Peel Strength	Internal standard WI/SP/Q/28	Machine Direction-92.4 N/50mm Cross Direction-95.7 N/50mm
Micro-Scratch Resistance (A & B)	EN 16094	MSR-B2 Rating in 160 Cycles
Castor Chair Test	ISO 4918	25000 Cycles Pass
Phthalates	CPSC-CH-C1001-09.4 with GS-MS Analysis	Not detected
VOC	1) Volatile Organic Compound (VOC), 2) Formaldehyde, 3) 1,3 Butadiene. All the value are within the limit as per the ISO 16000-9:2006 Standard.	Pass
Surface Burning Characteristics	ASTM E84-23	1. Class B for flame spread index. 2. Class A for smoke developed index.
Cleanability-Stain Resistance	NALFA 3.4	9 Rating
Wear Resistance	NALFA 3.7	8500 Cycles (with 0.3 mm Wear Layer)
Thickness Swell	NALFA 3.2	0%
Flexibility of Resilient Flooring Materials	ASTM F137	Passes 25 mm Mandrel
Residual Indentation	ASTM F3261	0.00 inch

Product Specification

Thickness	2 mm
Wear Layer Thickness	0.3 mm
Tile/Plank Sizes (Inch)	6" x 36"



Trademarks & Technologies

