



Earthy woods

The Organic Touch of Earth's Splendor

Welspun[®]
FLOORING



Earthy woods

Earthy Woods narrates the story and essence of mother earth and its hues in the form of divergent surfaces. It will remind an individual; the beauty & hues of nature through the binocular of organic textures and grains.



Experience Earth's Essence Underfoot...

Designed with
the essence of *Nature.*



RUBY | CTY00252



CELADON | CTY00250



SUNLIT YELLOW | CTY00251



COBALT | CTY00253



BUFF | CTY00256



MOCHA | CTY00255



GRAPHITE | CTY00254



STEEL GRAY | CTY00249





RUBY | CTY00252




Note: Savy Street collection design has been added to the room scene.

The images used are for illustration purpose only. The actual product appearance may vary.



COBALT | CTY00253



Note: Savy Street collection design has been added to the room scene.



SUNLIT YELLOW | CTY00251



Note: Savy Street collection design has been added to the room scene.

Coming together is
Beginning
Keeping together is
Process
Working together is
Success

MOCHA | CTY00255



Note: Savy Street collection design has been added to the room scene.



CELADON | CTY00250



Note: Savy Street collection design has been added to the room scene.



The Japanese Garden

Sophie Walker


GRAPHITE | CTY00254



Note: Savy Street collection design has been added to the room scene.



BUFF | CTY00256



Note: Savy Street collection design has been added to the room scene.



The images used are for illustration purpose only. The actual product appearance may vary.

STEEL GRAY | CTY00249



Note: Savy Street collection design has been added to the room scene.

PRODUCT SPECIFICATION

Collection Name	Earthy woods
Machine Gauge	PET
Yarn	1/12 Rainbow
Size (CM)	25X100
Pile Height	3.5-4.0
Total Thickness	5.0-5.5
Density	3900-4000
SPI	10.3
Tufting Weight (Oz)	15
Backing System	Welspun Ecolite or Comfortile
Indicates	+/- 5%

TEST REPORT SUMMARY

Test Name	Method	Test Name	Method
Delamination	ASTM D 3936	Static Electricity	AATCC 134-1996
Tuft Bind	ASTM 1335-67	Anti Static	ANSI/ESD S 7.1
Dimensional stability	ASTM D 7570	Castor Chair	DIN 54324
Pile weight	ASTM D 5848-07	Hexapod	ASTM D 5252-15
Pile density	ASTM D 5848-07	Static Coefficient	ASTM C 1028
Total thickness	ASTM D 6988-08	Dimensional stability (Aachen test)	DIN-STD-54318/ITTS-004
Pile height	ASTM D 5823-05a	Anti Soil	ASTM D 6540-05
Gauge	ASTM D 5793-13	Shampoo Fastness	AATCC 138
Tuft density	ASTM D 5848	Water Fastness	AATCC 107
Flammability (Pill Test)	ASTM D 2859	Velcro-Loops	ITTS 112
Flammability (Radiant Panel)	ASTM E 648-06	Heavy Traffic test (Walk test)	ASTM 6119-03
NBS Smoke Density (Flaming)	ASTM E 662-06	Sound transmission	ASTM C 423-17
Lightfastness	AATCC 16 E	Sound Absorption	ASTM C 423-17
Colour fastness to Ozone	AATCC 129	Static Loading	ISO 015/3415
Colour fastness to NO ₂	AATCC 164-2008	Green Carpet (VOC)	ASTM D 5116
Crocking Dry and Wet	AATCC 165-2008	Acoustic	BS EN ISO 354
Stain fastness	AATCC 175-2008/ITTS 002	Thermal Resistance	ASTM C 518

CARPET TILES ADVANTAGES



Easy To Install



Stain Protect



Fade Resistant



Less Lead Time



Offers Sound Absorption



Reduce Wastage During Installation



Made in India

TRADEMARKS & TECHNOLOGIES



Welspun Ecolite™

Welspun Ecolite™ backing are made up of lightweight PVC that not only reduces the overall weight significantly but ensures a 40% lower environmental footprint than traditional carpets. Despite that, this backing retains the highest performance standards.



Now also available with Healthy Floor™ (Optional).

We also have carpet tile options with antiviral properties. Tested and certified by ResInnova Labs, we are India's first antiviral carpet tiles. It kills 99.68% of human coronavirus due to a special coating of silver iron & titanium oxide. We make healthy floors.



Comfortile™M (Optional).

With Comfortile™ backing, our tiles come with a customized felt-back that not only offers great underfoot comfort but also sound absorption. Comfortile™ provides extra levels of protection and support for high levels of acoustic and ergonomic comfort.

CERTIFICATION



Welspun[®]

FLOORING

WELSPUN GLOBAL BRAND LTD,
SURVEY NO. 190, CHANDANVELLY, NEAR HYTHABAD,
SHABAD MANDAL, RANGA REDDY (DIST),
TELANGANA 501 503
INDIA

Contact us:
1800 - 120 - 1161
India: contact_flooring@welspun.com
Global: global_saleswfl@welspun.com

www.welspunflooring.com



Scan the QR code to explore
Earthy woods collection